


esscobathware.com
Document No.
SNW/ECS/24/355SNPP











TOD	1/1	<b>Ι</b> Ε\Λ/	
IUF	VI		

General Information	ı
---------------------	---

Scholar Information				
Product Code	ECS-WHT-355SNPP			
Brand	Essco			
Colour	White			
Туре	Anglo Indian-WC (s trap )			
Material	Ceramic-Vitreous China (VC)			
Product Specification				
Product Dimension	475x575x400 mm			
Bowl Opening (Inner Dimension)	375x230 mm			
Product Net Weight	18.8 kg			
Product Gross Weight	22.5 kg			

	Outlet
	Trap Distance
ı	

Inlet Hole And Outlet Hole

Dimension

Packaging Dimension

nternal	diameter	of inlet	hole	dia. Ø	50	± 3 n	nm
xterna	l diameter	of outle	et ho	le dia	Ø 1	00 +	5 mm

	Vertical distance between the Floor and the centre line of the inlet hole ≤ 355 mm
	Packed with Accessories
Product Features	Completet Trap galze,
Product reatures	Dual Flushing - 3/6 LPF

585x490x455 mm

Anti germ glaze.

Horizontal S-Trap

## ACCESSORIES INCLUDED

PP close seat cover	ECS-WHT-107N
Floor fixing screw	ZPS-SNS-FB01
Outlet Gasket	ZPS-BLK-GK02

## ACCESSORIES RECOMMENDATION

Wall Hung Cistern WHE-WHT-183NL

## CARE AND CLEANING GUIDELINES

- ¬ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ¬ Carefully inspect the new product for damage before installation.
- ¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ¬ Risk of external leakage. Do not lift or rock the bowl after placement.
- $\neg$  Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ¬ Do not allow cleaners to sit or soak on the product.
- ¬ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ¬ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- $\neg$  Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

## QUALITY MANAGEMENT SYSTEM - ISO 9001





DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.
# For Installation Refer Actual Product