| associate | 45550 |
|--|--|
| esscobathware.com | ESSCO « Jaguar |
| Document No. | |
| SNW/ECS/24/453 | |
| | |
| | |
| | |
| <mark>405</mark> | |
| | |
| | |
| | |
| 210 | |
| 9 | |
| | |
| | |
| TOP VIEW | SIDE VIEW BACK VIEW |
| General Information | |
| Product Code | ECS-WHT-453 |
| Brand | Essco |
| Colour | White |
| Туре | Orissa Pan WC |
| Material | Ceramic-Vitreous China (VC) |
| Product Specification | |
| Product Dimension Bowl Opening (Inner Dimension) | 405x510x250 mm 410x190 mm |
| Product Net Weight | 12.0 kg |
| Product Gross Weight | 12.5 kg |
| Packaging Dimension | 610x265x470 mm |
| Outlet | Vertical |
| oulet | Internal diameter of inlet hole dia. $Ø 50 \pm 3$ mm |
| Inlet And Outlet Hole Dimension | External diameter of outlet hole dia. Ø 100 \pm 5 mm |
| | Vertical distance between the Bowl bottom edge and the centre line of the inlet hole ≤ 215 mm |
| Dreduct Fratures | |
| Product Features | Anti germ glaze. |
| ACCESSORIES RECOMMENDATION | |
| Cistern | WHE-WHT-183L |
| CARE AND CLEANING GUIDELINES | |
| | icts are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use |
| thereafter. | manded that two percent held it while it is being fixed |
| | nmended that two persons hold it while it is being fixed. |
| ¬ Carefully inspect the new product | ior damage before installation. |
| Risk of product damage. Over tight | ening may cause breakage or chipping of vitreous china. |
| - Risk of external leakage. Do not lift or rock the bowl after placement. | |
| - Always test your cleaning solution | on an inconspicuous area on the product before applying it to the entire surface. |
| ¬ Do not allow cleaners to sit or soal | ton the product. |
| - Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad. | |
| – Wipe surfaces clean and rinse completely with water immediately after applying cleaners. | |
| - Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion. | |
| → Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth. | |
| QUALITY MANAGEMENT SYSTEM - I | 50 9001 CE |
| DISCLAIMER: Our every effort has be | en made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. |
| - | ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. |