



<b>Product Code</b>	APR-CHR-101055NK
<b>Description</b>	Exposed Parts Kit of Single Lever Diverter Consisting of Operating Lever & Wall Flange (with O-rings) only (Suitable for Item ALE-055)
<b>Recommended Water Pressure</b>	0.5 Bar - 5 Bar
<b>Material Composition Specification in Percentage</b>	<p><b>Brass Rod as per IS:319-1989</b>            Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>Brass Sheets as per IS:410-1977</b>            Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)</p> <p><b>ABS</b> - Specific Gravity (g/cm<sup>2</sup>) - (1.06-1.10), Melt Mass Flow Rate (g/10 min.) - (20-26), Rockwell Hardness - (95-115), DTUL @ 66 psi (0.45 MPa) (0C) - (78-102)</p> <p>NBR 70 - Rubber Parts</p>
<b>Finish</b>	Plating: Nickel-8.0 micron Chromium-0.20 micron Salt Spray (300 hrs + Validated) Adhesion (Pass)
<b>Available Colour Finishing</b>	Chrome (CHR)

**DISCLAIMER:** Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. Jaquar reserves the right to make the necessary amendments at any time without prior notice.