

GENERAL INFORMATION		
Product Code	ECS-WHT-557NSSPPSM	
Brand	Essco	
Colour	White	
Туре	EWC S-Trap	
Material	Ceramic-Vitreous China (VC)	
PRODUCT SPECIFICATION		
Product Dimension	345x570x415 mm	
Bowl Opening (Inner Dimension)	250x310 mm	
Product Net Weight	20.5 Kg	
Product Gross Weight	23.8 kg	
Packaging Dimension	565x430x440 mm	
Outlet	Vertical	
Trap Distance	S Trap	
Inlet Hole And Outlet Hole Dimension	Internal diameter of inlet hole dia. Ø 50 ±3 mm	
	External diameter of outlet hole dia. Ø 100 ± 5 mm	
	Vertical distance between the Floor and the centre line of the inlet hole ≤ 380 mm	
PRODUCT FEATURES		
Product Features	Square Shaped Bowl Design with Efficient Flushing Complete Trap Wash PP Soft close seat cover Water Usage- Dual Flushing - 3/6 LPF Smooth Glaze Surface	
ACCESSORIES INCLUDED		
Seat Cover	ORS-WHT-101S	
Outlet gasket	ZPS-BLK-GK02	
Floor fixing screw	ZPS-MST-FB11	

Seat Cover	ORS-WHT-101S
Outlet gasket	ZPS-BLK-GK02
Floor fixing screw	ZPS-MST-FB11

ACCESSORIES RECOMMENDATION

Wall Hung Cistern	ESH-WHT-184N,ESH-WHT-184NL,ESH-WHT-184NT,ESH-WHT-184AN,
	ESH-WHT-184ANL,ESH-WHT-184ANT,ESH-WHT-184NBTT,ESH-WHT-184NBTL

CARE AND CLEANING GUIDELINES

- , Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ¬ Carefully inspect the new product for damage before installation. Recommended to inspect the sanitaryware with wooden Hammer.
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china. Recommended to use hard rubber & nylon spacer in between ceramic & metal fixtures.
- Risk of external leakage. Do not lift or rock the bowl after placement.
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- Do not allow cleaners to sit or soak on the product.
- use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- . Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.
- Recommended to use Genuine Accessories.

QUALITY MANAGEMENT SYSTEM - ISO 9001



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. All dimensions are in mm (Tolerance \pm 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product.Last modified on 19 August 2025.