esscobathware.com	
Document No.	
SNW/ECS/24/817	- "UKO"
51110/203/24/01/	•
	·
	415
1	
, <del>P</del>	
Ø35-	
₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽ ₽	
Ø45-	ι
043	
	SIDE VIEW
TOP VIEW	BACK VIEW
General Information	
Product Code	ECS-WHT-817
Brand	Essco
Colour	White
Туре	Wall Hung Basin with pedestal
Material	Ceramic-Vitreous China (VC)
Product Specification	
Product Dimension	515x415x190 mm
Basin Inner Dimension	495X295X150 mm
Product Net Weight	11.5 kg.
Product Gross Weight	12.5 kg.
Packaging Dimension	510x200x420 mm
Outlet	Vertical
	Tap hole dia. Ø 35 $\pm$ 2 mm
Tap Hole And Outlet Hole Dimension	Internal diameter of outlet hole dia. Ø45 +2/-1 mm
	Horizontal distance between the center line of the tap hole and the center line of the waste outlet hole $\leq$ 145 mm
	Round Shape Basin. With Tap Hole & Over flow hole,
Product Features	Packed Accessories ,Anti germ glaze.
ACCESSORIES INCLUDED	
Overflow hole cap	ZPS-WHT-9012
Basin fixing screw	ZPS-MST-RB03
CARE AND CLEANING GUIDELINES	
- Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.	
- The product is heavy and it is recommended that two persons hold it while it is being fixed.	
- Carefully inspect the new product for damage before installation.	
- Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.	
$\neg$ Risk of external leakage. Do not lift or rock the bowl after placement.	
ו אוא טי באנכוזים ובמהפצב. ביט ווטר ווור טו זטרא נווב שטשיו מוכו  וומרפווופוור.	
- Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.	
$\neg$ Do not allow cleaners to sit or soak on the product.	
- Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.	
- Wipe surfaces clean and rinse completely with water immediately after applying cleaners.	
- Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.	
- Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.	
QUALITY MANAGEMENT SYSTEM - IS	50 9001 CE
	500
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice.	
# For Installation Refer Actual Product	