



|   |  |
|---|--|
| <b>Product Code</b>   | SAE-CHR-1931SH555  |
| <b>Description</b>  | Hand Shower Pack (Multi flow 80mm round shape hand shower with 1.5M long spirochrome flex hose & wall bracket, 1931, 547D8 & 555)  |
| <b>Flow Rate</b>  | Normal - 14.78 LPM @ 3 bar<br>Massage - 7.59 LPM @ 3 bar   |
| <b>Flow regulator</b>   | By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM, GB-8.0 LPM & GC-12.0 LPM @ 4.0 Bar pressure) one can regulate the flow rate.  |
| <b>Recommended Water Pressure</b>   | 1.0 Bar - 3.0 Bar  |
| <b>Spray Modes</b>  | Normal and Massage functions   |
| <b>Material Composition Specification in Percentage</b>   | <p><b>Brass Rod as per IS:319-1989</b><br/>Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>SS Sheet as per AISI 304</b><br/>Ni (8.000 - 11.000), Cr (18.000 - 20.000), Mn (0.0 - 2.000), C (0.0 - 0.080), Iron (Remainder)</p> <p><b>ABS Specification</b><br/>Specific Gravity g/cm<sup>2</sup> (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)</p> |
| <b>Technology</b>   | <b>Advanced Rubit</b> - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel.  |
| <b>Finish</b>   | Salt Spray (200 hrs + Validated)<br>Adhesion (Pass)  |
| <b>Available Finishing</b>  | CHROME (CHR)   |
| DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice. |  |